

ABS Ice Coffee

Parts list

- Quantity 4 Part #28075 (long thread fingers) \$20.12 Total
- Quantity 4 Part #1067972 (black spacers) \$2.24 Total
- If you do not have the **42oz Cup Tube Sleeve**, please order **1 of Part#28377 (\$136.25)** in addition

Order Information: 1-800-241-2653 (ask for a Sr. Technician) (24 hours a day / 7 days a week)
:

Tool(s) required

- 5/16" Nut Driver or 5/16" socket for acorn nuts on outside cup tube

INSTALLATION

- Replace original **42oz** cup tube fingers with the new fingers and spacers (pt#28075 & pt#1067972). Do **not** use the original fingers that come with the new 42 oz cup tube sleeve.

PROGRAMMING on ABS

1. Place unit into the "Manual" mode (should already be in)
2. Press the ▼ (down arrow) once to prompt the password
3. Enter the password (Flavor buttons 1,2,3,4)
4. Press "**Enter**" two times
5. Press ▼ (down arrow) once to "**Setup**"
6. Press "**Enter**" two times
7. Press ▼ (down arrow) 4 times to (**6 Adjust Ice**)
8. Press "**Enter**" twice
9. Enter into **Cup Portion**
10. Navigate to **XL** by pressing the > button and select it
11. Press ▼ (down arrow) to assigned the 'norm' to approximately **45**
12. Press Enter to accept the new number
13. Hit Back/Clear several times until the display asks for '**Save**'
14. Press Enter twice
15. Press Manual/Auto key to return to Automatic mode

PROGRAMMING on POS

1. The functionality on the POS register should be rang up as "**42 oz Brew Tea or 42 oz Iced Tea**"
the text should edited to "**Ice Coffee**"

Ice Level Guide: These numbers are based on a Manitowoc Ice Machine (half-diced) cubes

- Step 11 set to **25** will dispense ½ cup of Ice
- Step 11 set to **40** will dispense 1" below rim of cup
- Step 11 set to **45** will dispense ¾" below rim of cup
- Step 11 set to **50** will dispense a FULL cup of Ice

My recommendation is between **40-45** but depends on amount needed for the desired product